FIELD EMITTER ARRAY BASED DICKE SWITCH ARRAY FOR MM-WAVE



RADIOMETRIC SYSTEMS

Contract No: N00014-94-C-0243

MONTHLY REPORT NO. 3

Period Ending December 1994

Prepared For

BALLISTIC MISSLE DEFENSE ORGANIZATION

OFFICE OF NAVAL RESEARCH

CODE 251A

BALLSTON TOWER ONE

800 NORTH QUINCY STREET

ARLINGTON VA 22217-5660

Prepared By.

Princeton Microwave Technology Inc.

3564 Quakerbridge Road

Mercerville. NJ 08619

DISTRIBUTION STATEMENT II

Approved to public released

Distribution Unlimited

19951031 035

TASK 1.3. Software Analysis of Array.

The preliminary analysis of the array has been completed. Based on this analysis an array has been designed and a prototype circuit is being readied. The array will be first tested statically so that its performance is documented for comparison later. In order to conduct the testing of the array, illumination and receiving horn antennas at 30 Ghz have been designed. Once the transmission characteristics of the array have been completed, the final array with the switches will be implemented to test the overall objective of the program.

TASK 2.0 Fabrication

A preliminary design of the array has been completed. A protoype array has been layed out for fabrication in order to test its transmission characteristics. The Experiment will consist of the array illuminated by circular horn for the source and the energy will be received by a second circular horn, after it has passed through the array. The design of the horns have also been concluded and submitted for fabrication.

Plans for next month:

During the next month the testing of the switch will be completed. It is expected to complete the testing of

the switch array in its transmission mode.



TASK 1.3. Software Analysis of Array.

The preliminary analysis of the array has been completed. Based on this analysis an array has been designed and a prototype circuit is being readied. The array will be first tested statically so that its performance is documented for comparison later. In order to conduct the testing of the array, illumination and receiving horn antennas at 30 Ghz have been designed. Once the transmission characteristics of the array have been completed, the final array with the switches will be implemented to test the overall objective of the program.


Figures 1 and 2 shown the specifications of the planar array and its radiation pattern. Figures 3,4,5 and 6 detail the design parameters associated with the test horn antennas.


TASK 2.0 Fabrication

A preliminary design of the array has been completed. A protoype array has been layed out for fabrication in order to test its transmission characteristics. The Experiment will consist of the array illuminated by circular horn for the source and the energy will be received by a second circular horn, after it has passed through the array. The design of the horns have also been concluded and submitted for fabrication.

Plans for next month:

During the next month the testing of the switch will be completed. It is expected to complete the testing of the switch array in its transmission mode.





Array Specifications

Number of elements in x: 2 in y: 2 Element spacing (cm) in x: .5 in y: .5 Operating frequency (GHz): 30

Amplitude Distribution: Uniform

Phase Distribution: Broadside Beam Phase shift in x: 0.0 in y: 0.0 Scan angle: 0= 0.0 ø= 0.0

Element type: Rectangular Patch


Polarization of elements: (X/Y)? X Resonant length (cm): .3 Patch width (cm): .3

Pattern cut: ø (deg)= 5 Pattern increment (deg): 1

Use 14 and Enter for menus;

Esc to backup or quit


FiguRE 1: 2x2 ARRAY AT 30 GHZ



Use ↔ to move cursor PrtSc for EGAD Esc to quit


E-theta = 0.99 dB E-phi = -21.16 dBat Theta = 0.0 deg.


Figure 2: Pattern Associated With Figure 1



Input Data

Enter axial horn length (to apex)(cm): 20 Enter the frequency (GHz): 30 Enter aperture radius (cm): 3.9 Enter pattern increment (deg): 2






Esc to backup or quit


Use 11 and Enter for menus;

Figure 3: Muminating Horn at 30 GHZ



E-plane = 0.00 dB H-plane = 0.00 dB at Theta= 0.0 deg.

Figure 4: Pattern of Murrinating Conical Horn



Input Data

Enter the frequency (GHz): 30

Enter E-plane aperture dimension (cm): 6

Enter H-plane aperture dimension (cm): 6

Enter axial horn length (to apex)(cm): 20

Enter pattern increment (deg): 2

Plot Options Plot type (P/R): R

Horn Characteristics


Maximum phase error is 81.0° Optimum E-plane dimension is 6.3 cm The directivity is 24.9 dB

Use 11 and Enter for menus;

Esc to backup or quit

Figure 5: illuminating

Han at 30 GHz



Use ++ to move cursor PrtSc for EGAD Esc to quit

E-plane = 0.09 dB H-plane = 0.09 dB at Theta= 0.0 deg.

Figure 6: Pattern of Rectangular Muminating Horn at 30 9 Hz.





OFFICE OF THE UNDER SECRETARY OF DEFENSE (ACQUISITION) DEFENSE TECHNICAL INFORMATION CENTER CAMERON STATION ALEXANDRIA, VIRGINIA 22304-6145

IN REPLY REFER TO

DTIC-OCC

SUBJECT: Distribution Statements on Technical Documents

OFFICE OF NAVAL RESEARCH CORPORATE PROGRAMS DIVISION

ONR 353 TO:

800 NORTH QUINCY STREET ARLINGTON, VA 22217-5660

1. Reference: DoD Directive 5230.24, Distribution Statements on Technical Documents, 18 Mar 87.

2. The Defense Technical Information Center received the enclosed report (referenced below) which is not marked in accordance with the above reference.

MONTHLY REPORT #3 N00014-94-C-0243 TITLE: FIELD EMITTER ARRAY BASED DICKE SWITCH ARRAY FOR

NIM-WAVE

- 3. We request the appropriate distribution statement be assigned and the report returned to DTIC within 5 working days.
- 4. Approved distribution statements are listed on the reverse of this letter. If you have any questions regarding these statements, call DTIC's Cataloging Branch, (703) 274-6837.

FOR THE ADMINISTRATOR:

1 Encl

GOPALAKRISHNAN NAIR Chief, Cataloging Branch

FL-171 Jul 93

DISTRIBUTION STATEMENT A:

APPROVED FOR PUBLIC RELEASE: DISTRIBUTION IS UNLIMITED

DISTRIBUTION STATEMENT B:

DISTRIBUTION AUTHORIZED TO U.S. GOVERNMENT AGENCIES ONLY; (Indicate Reason and Date Below). OTHER REQUESTS FOR THIS DOCUMENT SHALL BE REFERRED TO (Indicate Controlling Dod Office Below).

DISTRIBUTION STATEMENT C:

DISTRIBUTION AUTHORIZED TO U.S. GOVERNMENT AGENCIES AND THEIR CONTRACTORS; (Indicate Reason and Date Below). OTHER REQUESTS FOR THIS DOCUMENT SHALL BE REFERRED TO (Indicate Controlling Dod Office Below).

DISTRIBUTION STATEMENT D:

DISTRIBUTION AUTHORIZED TO DOD AND U.S. DOD CONTRACTORS ONLY; (Indicate Reason and Date Below). OTHER REQUESTS SHALL BE REFERRED TO (Indicate Controlling DoD Office Below).

DISTRIBUTION STATEMENT E:

DISTRIBUTION AUTHORIZED TO DOD COMPONENTS ONLY; (Indicate Reason and Date Below). OTHER REQUESTS SHALL BE REFERRED TO (Indicate Controlling DoD Office Below).

DISTRIBUTION STATEMENT F:

FURTHER DISSEMINATION ONLY AS DIRECTED BY (Indicate Controlling DoD Office and Date Below) or HIGHER DOD AUTHORITY.

DISTRIBUTION STATEMENT X:

DISTRIBUTION AUTHORIZED TO U.S. GOVERNMENT AGENCIES AND PRIVATE INDIVIDUALS OR ENTERPRISES ELIGIBLE TO OBTAIN EXPORT-CONTROLLED TECHNICAL DATA IN ACCORDANCE WITH DOD DIRECTIVE 5230.25, WITHHOLDING OF UNCLASSIFIED TECHNICAL DATA FROM PUBLIC DISCLOSURE, 6 Nov 1984 (Indicate date of determination). CONTROLLING DOD OFFICE IS (Indicate Controlling Dod Office).

The cited documents has been reviewed by competent authority and the following distribution statement is hereby authorized.

OFFICE OF NAVAL RESEARCH CORPORATE PROGRAMS DIVISION (Statement) (Controlling DoD Office Name) ONR 353 800 NORTH QUINCY STREET ARLINGTON, VA 22217-5660 (Reason) (Controlling DoD Office Address. DEBRA T. HUGHES City, State, Zip) DEPUTY DIRECTOR [1 9 SEP 1995 CHATE PROGRAMS OFFICE *MMMA / MMMAL* Signalure & Typed Name) (Assigning Office) (Date Statement Assigned)